

Model 240 Central Mixer

Mobile · Self-contained · Self-erecting

The Highly mobile 240 is self-erecting and takes only minutes to set up. The wheel and suspension unit may be removed by pulling four pins and rolling out the complete unit. The mixer is powered by a 350 hp Diesel/Hydraulic power unit. The mixer drum is designed to mix 10 cubic yards of five inches slump concrete without spillage.

The track and gathering hopper are raised into working position by hydraulic rams. The gathering hopper is ten feet above the ground when the mixer is set up at its lowest level. Four hydraulic cylinder jacks will lift the unit to desired height. Six screw jacks furnish permanent support for the unit.

Part of the mixing time may be gained while the mixer is being elevated to discharge point. Temper water may be added while the mixer is being elevated. The mixer is not supported by wheel rolls. The drum is attached to the outer race of a sealed ball bearing that is surrounds the drum. The inner race of the bearing is attached to the mixer support ring that is trunnion mounted to the frame. The bearing has a basic static thrust rating of over 2,000,000 pounds.



CEMCO, INC.

R.R. 3 Box 14
Olney, TX 76374
940-564-5855
Fax: 940-564-5546
info@cemcoinc.com

- Power - 350 HP Diesel Hydraulic
- Capacity 12 Cu. Yd. Input, 10 Cu. Yd. Output
- Mixer Drum 3/8" A-36
- Suspension - 3 – 20,000# Axles
- Mixer Driver – Dual Pinion – direct Hydraulic
- Width – 13'4"
- Travel Height – 14'4"
- Length – 35'
- Weight 66,000 lbs.

With the advent of the new Cemco Central Mix the concrete ready mix and paving business will never be the same.



CONEXPO-CON/AGG
Show of 2008

*240 Central Mixer
is capable of
producing 240 cu.
Yds. Per hour*



Cemco, Inc. revolutionized the concrete industry with a line of mobile batching and mixing equipment that continually finds a way to reinvent the standards of speed, accuracy and efficiency.

CEMCO, INC.
R.R. 3 Box 14
Olney, TX 76374
940-564-5855
Fax: 940-564-5855
info@cemcoinc.com